# **DESIGNMIX**<sup>™</sup>: Mortar Mix

TYPE M, 80 lb – ITEM# MBØ8ØDMTMØØØ
TYPE M, 3500 lb – ITEM# MB35ØDMTMØØØ
TYPE N, 80 lb – ITEM# MBØ8ØDMTNØØØ
TYPE N, 3500 lb – ITEM# MB35ØDMTNØØØ
TYPE S, 80 lb – ITEM# MBØ8ØDMTSØØØ
TYPE S, 3500 lb – ITEM# MB35ØDMTSØØØ

#### PRODUCT DESCRIPTION

**DESIGNMIX™** Professional-Grade Mortar Mix is a specially blended portland cement/lime based mortar mix that, when prepared properly, will result in a mortar that conforms to the Property Specification requirements of ASTM C270 (Standard Specification for Mortar for Unit Masonry) and the requirements of ASTM C1714/C1714M (Standard Specification for Preblended Dry Mortar Mix for Unit Masonry). **DESIGNMIX** Professional-Grade Mortar Mix is appropriate for use with brick and concrete block. Properties and uses of mortar vary with specific mortar type. Each **DESIGNMIX** Professional-Grade Mortar Mix bag is stamped with the mortar mix type as specified by ASTM C270.

## **SPECIFICATION STANDARDS**

The requirements for compressive strength, water retention and air content as prescribed by ASTM C270 are listed in the table below. All ASTM C270 requirements are for mortar that is laboratory prepared, cured, and tested.

ASTM C270 Property Specification Requirements (for Laboratory prepared and tested Mortars)									
Mortar	Туре	Avg. Compressive Strength @ 28 days, min., psi (MPa)	Water Retention, min. %	Air Content, max. %					
Portland Cement - Lime	M	2500 (17.2)	75	12					
Portland Cement - Lime	S	1800 (12.4)	75	12					
Portland Cement - Lime	N	750 (5.2)	75	14					

**DESIGNMIX** *Professional-Grade Mortar Mix* is designed for maximum workability with both clay and concrete masonry units. **DESIGNMIX** *Professional-Grade Mortar Mix Type M* is for use at, below or above grade applications. **DESIGNMIX** *Professional-Grade Mortar Mix Type S* is designed for use at or above grade applications. **DESIGNMIX** *Professional-Grade Mortar Mix Type N* is designed for use above grade.

## **OTHER LIMITATIONS**

When selecting a **DESIGNMIX** *Professional-Grade Mortar Mix* for particular type and properties, follow local building code requirements.

## **CAUTION**

Do not place **DESIGNMIX** *Professional-Grade Mortar Mix* if the temperature is less than 41° F (5° C) or more than 95° F (35° C). Protect the **DESIGNMIX** *Professional-Grade Mortar Mix* for the first 72 hours after placement.

#### **STORAGE OF MATERIALS**

Store **DESIGNMLX** *Professional-Grade Mortar Mix* in such a manner as to prevent deterioration or intrusion of foreign material. In general, store bags in a dry area, elevated above the bare ground or floor on pallets or other suitable protection. Protect from rain, snow and other sources of moisture.

## **MIXING INSTRUCTIONS**

Mix bag contents with the minimum amount of potable water needed to produce a workable consistency. In general, first place 1 gallon of water in a mechanical batch mixer, then add **DESIGNMIX** *Professional-Grade Mortar Mix*. Continue adding water and **DESIGNMIX** *Professional-Grade Mortar Mix* as required to get appropriate consistency of mortar and quantity needed. Mix for 3 to 5 minutes. Hand mixing may be permitted by the specifying authority with approved procedures.

## **YIELD & COVERAGE**

Each 80 lb bag of DesignMix Professional-Grade Mortar Mix will yield approximately 0.74 cu ft of mortar when mixed to a workable consistency, that will cover approximately 40 standard brick or 15 standard 8" block.

Mutual • Target L.L.C. is a partnership of Mutual Materials Co. and Target Products Ltd. Performance is affected by many factors, including storage, method and conditions of application and use. User testing is ESSENTIAL to determine suitability of product for intended method of application and use. Mutual • Target's SOLE WARRANTY is that the product has been manufactured to specifications. No oral or written information or advice shall increase this warranty or create new warranties. Mutual • Target's SOLE LIABILITY is to replace product proved defective. In no event shall Mutual • Target be liable for any consequential, indirect or other damages whether arising from negligence or otherwise.

# **MUTUAL MATERIALS LOCATIONS**

WASHINGTON		OREGON &		IDAHO		WESTERN CANADA SALES	
Auburn Bellevue	(253) 939-0403 (425) 452-2311	SW WASHIN Bend	(541) 312-3623	Hayden / Co	eur d'Alene area (208) 762-3230	Langley	(604) 888-0555
Bellingham	(360) 676-2881	Clackamas	(503) 905-2011	MONTANA			
Burlington Mukilteo Olympia	(360) 707-2915 (425) 353-9686 (360) 357-3344	Durham Hillsboro Salem	(503) 906-2332 (503) 640-4732 (503) 375-3129	Kalispell Missoula	(406) 755-5716 (406) 549-2011		
Tacoma (Park	• •	Vancouver	(360) 573-2513				
Port Orchard Redmond Spokane	(360) 876-2313 (425) 867-1493 (509) 922-4451				Trusted S	UALM ince 1900 ualmaterials.c	ATERIALS