



FIREBRICK



Fireplace Accessories



FIREPLACES



PIZZA OVENS

Mutual Materials Firebrick is manufactured to comply with the physical properties and characteristics specified by ASTM C 1261, Standard Specification for Firebox Brick for Residential Fireplaces. They are specifically designed for use in wood inserts or stoves and are not meant for exposed outdoor use, veneer wall or horizontal paving applications.

Our Firebrick is manufactured from a special blend of clay and shale to produce a hard-fired refractory brick capable of resisting the heat produced in a common fireplace. Also suitable for pizza ovens.

Maximum recommended temperature for fireplaces: 2700° F.

Product	Dimensions	Color	Wt/Piece	Wt/Box
Firebrick Standard	9" L x 4 1/2" W x 2 1/2" h 22.9 cm L x 11.43 cm W x 6.35 cm H	Buff	6.5 lbs 2.94 kg	25-40 lbs 11-18 kg
Firebrick Split	9" L x 4 1/2" W x 1 1/4" h 22.9 cm L x 11.43 cm W x 3.2 cm H		4 lbs 1.81 kg	

Firebrick Standard

9" L x 4 1/2" W x 2 1/2" h
22.9 cm L x 11.43 cm W x 6.35 cm H

**Firebrick Split**

9" L x 4 1/2" W x 1 1/4" h
22.9 cm L x 11.43 cm W x 3.2 cm H

**MUTUAL MATERIALS LOCATIONS**

For product information and customer service, call **1-888-MUTUALØ (688-8250)**.

WASHINGTON		OREGON		IDAHO		MONTANA	
Auburn	Port Orchard	Bend		Boise		Missoula	
Bellevue	South Seattle	Clackamas		Hayden			
Bellingham	Spokane	Durham					
Marysville	Tacoma (Parkland)	Portland					
Olympia (Tumwater)	Vancouver, WA	Salem					

**MUTUAL MATERIALS®**